## Claims

	•	-
10		
1		

- 1.A system for synchronization of the digital transmission of analog modem signals, comprising:
- (A)a base unit in communication with an extension unit; wherein
- (B) said base unit further comprises:
- (1)a base line interface circuit in communication with a modem;
- (2)a base analog to digital converter connected to said base line interface circuit;
- (3)a base timing / framing circuit connected to said base analog to digital converter; and
- (4)a base transceiver connected to said base timing / framing circuit, wherein said base transceiver provides a signal to said extension unit.

[c2]

2.A system for synchronization of the digital transmission of analog modem signals, as recited in claim 1, wherein said base transceiver is an A/C Power Line Carrier transceiver.

[c3]

3.A system for synchronization of the digital transmission of analog modem signals, as recited in claim 1, wherein said base transceiver is an RF transceiver.

[c4]

4.A system for synchronization of the digital transmission of analog modem signals, as recited in claim 1, wherein said base transceiver receives a signal from said extension unit.

[c5]

5.A system for synchronization of the digital transmission of analog modem signals, as recited in claim 1, further comprising a base formatting circuit in connected to said base transceiver.

[c6]

6.A system for synchronization of the digital transmission of analog modem signals as recited in claim 1, further comprising a base Digital to Analog converter connected to said base formatting circuit.

[c7]

- 7.A system for synchronization of the digital transmission of analog modem signals, comprising:
- (A)a base unit in communication with an extension unit; wherein
- (B) said extension unit further comprises:
- (1)an extension line interface circuit in communication with a user modem;
- (2)an extension analog to digital converter connected to said extension line interface circuit;
- (3)an extension timing / framing circuit connected to said extension analog to digital converter; and
- (4)an extension transceiver connected to said timing / framing circuit, wherein said extension transceiver provides a signal to said base unit.

[c8]

8.A system for synchronization of the digital transmission of analog modem signals, as recited in claim 7, wherein said extension transceiver is an A/C Power Line Carrier transceiver.

[c9]

9.A system for synchronization of the digital transmission of analog modem signals, as recited in claim 7, wherein said extension transceiver is an RF transceiver.

[c10]

10.A system for synchronization of the digital transmission of analog modem signals, as recited in claim 7, wherein said extension transceiver receives a signal from said base unit.

[c11]

11.A system for synchronization of the digital transmission of analog modem signals, as recited in claim 7, further comprising an extension formatting circuit in connected to said extension transceiver.

[c12]

12.A system for synchronization of the digital transmission of analog modem signals as recited in claim 7, further comprising an extension Digital to Analog converter connected to said extension formatting circuit.

[c13]

- 13.A method of synchronizing the digital transmission of analog modem signals, comprising:
- (A)generating a recreation clock signal from a received start bit of an asynchronous transmission:
- (B)detecting said received start bit;
- (C)receiving said start bit and a digital data signal serially from a transmission medium;
- (D)converting said received digital data signal to an analog format; and
- (E)transmitting a second digital data signal via a return path.

[c14]

14.A method of synchronizing the digital transmission of analog modem signals, as recited in claim 13, wherein said transmission medium is an A/C power line.

[c15]

15.A method of synchronizing the digital transmission of analog modem signals, as recited in claim 13, wherein said transmission medium is an over the air RF signal.